



Corotop FIX PRO

Single-sided tape for bonding membranes

Single-sided adhesive tape produced from the acrylic dispersion reinforced with polyester fibres to have better adhesiveness properties. Made of polypropylene coated with a special adhesive based on acrylic dispersion. Resistant to UV radiation and ageing processes.

Advantages

- ✓ high bonding strength
- ✓ high temperature resistance
- ✓ high weather resistance

Application

- ✓ for bonding and fixing the polypropylene and polyethylene plastic foils
- ✓ for connecting foil with plastics, concrete, wood and metal
- ✓ to be used inside building structures



Characteristics

Material	LDPE, acrylic adhesive, reinforced with scrim	Peel strength of joints	≥ 30 N /25 mm
Colour	white, red overprint	Elongation	100 %
Length	25 m	Temperature of application	+5°C to +30°C
Width	60 mm	Temperature resistance	-30°C to +100°C
Thickness	0,30 - 0,33 mm		

Installation

1. Clean the surface from dust and other contamination.
2. Do not tighten the tape on the bonding surface.
3. Observe the recommended temperature for using.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage.

Packaging

Quantity per box (pcs.):	10
Quantity on a pallet (pcs):	700