#### **Technical data sheet**

# **Corotop FIX**

## Single-sided tape for bonding membranes

The multiseasonal single-sided adhesive tape. It is produced from the acrylic dispersion reinforced with polyester fibres to have better adhesiveness properties. Made of polypropylene coated with a special adhesive based on acrylic dispersion. Resistant to UV radiation and ageing processes.

#### **Advantages**

- high bonding strength
- extensible
- high weather resistance

# **Application**

- for bonding and fixing the polypropylene and polyethylene plastic foils
- ✓ for connecting foil with plastics, concrete, wood and metal
- to be used inside building structures

#### **Characteristics**

Material	LDPE, acrylic	Peel strength of joints	≥25 N /25 mm
Colour	adhesive white, red overprint	Elongation	100 %
Length	25 m	Temperature of application	+10°C to +30°C
Width	50 mm		
Thickness	0,26 - 0,29 mm	Temperature resistance	-30°C to +100°C

#### Installation

1 Clean the surface from dust and other contamination.

2. Do not tighten the tape on the bonding surface.

3. Observe the recommended temperature for using.

### Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage.

# Packaging

Quantity per box (pcs.):12Quantity on a pallet (box./pcs):70/840

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.



