Corotop Oplot

Multi-functional mat in the form of a braid

Three-dimensional multifunctional mat in the form of a braid, consisting of individual polypropylene fibres intertwined in a pointed form. It acts as a separation and drainage layer. It provides air circulation and the ability to drain water and moisture from the metal roofing or façade.

Advantages

- ✓ lightweight and comfortable to install
- ✓ suppresses the noise of precipitation
- ✓ protects the initial roofing



- ✓ for ventilated, insulated, uninsulated, and boarded pitched roofs
- ✓ or metal covers made of standing seam
- ✓ in ventilated and non-ventilated metal façades



Characteristics

polypropylene
250 g/m ² ±8 %
black
1,4 m
30 m

Thickness at 2 kPa	7,5 mm
Reaction on fire	class E
Tensile strength. along/ across	50 / 25 N/50mm
Elongation, along/across	70 / 40 %
Temperature resistance	-20° C to 80 °C

Packaging

Rolls/squere meter per pallet (rol/m 2): 9/ 378
Pallet dimension: length × width × height (m): 1,20 x 0,80 x 1,60

Storage

The rolls should be stored in ventilated, free from moisture place. Protect from chemical detergents and high temperatures The rolls must be transported in covered means of transport, protected from damage.

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.